

ESS Container

5.016 MWh

Liquid-cooled energy storage system



Liquid-cooled energy storage system based on HiTHIUM prismatic LFP ESS Cells 314 Ah with very high cyclic lifetime.

Improved safety characteristics and specially optimised for the highest requirements on safety, reliability and performance. Suitable e.g. for industrial, utility, and grid serving applications.

- Product certifications:
IEC 62619, IEC 62477, IEC 63056, IEC 61000, UL 1973, UL 9540A, UN 38.3
- Company certifications:
ISO 9001, ISO 14001, ISO 45001, SA 8000
- Environmental Compliance:
RoHS, REACH, Cobalt free

High safety

- High thermal stability thanks to liquid cooling
- Multi-stage, active fire protection system, compliance to NFPA 855
- Use of highly safe prismatic HiTHIUM LFP cells
- Dedicated cell monitoring and protection system

Low LCOS (Levelised Cost of Storage)

- Excellent thermal management improves energy throughput by ensuring optimal operating temperature
- Highly integrated: including thermal management system, fire protection system, BMS, etc.
- Supports back to back and side by side installations

ESS Container

5.016 MWh

Liquid-cooled energy storage system based on prismatic LFP cells with very high cyclic lifetime



GENERAL

Configuration	6*2P416S
Cooling Method	Liquid Cooling
BMS Communication	CAN, RS485, Ethernet
Gravimetric ED	≥ 125 Wh/kg (≥56.7 Wh/lbs)
Volumetric ED	≥ 117 Wh/L (≥442.9 Wh/gal)
Application Altitude	≤ 4,000 m (≤13123 ft)

ELECTRICAL

Nominal Voltage	1,331.2 V
Operating Voltage	1,040 V ... 1,500 V
Nominal Energy	5016 kWh ^{1,2}
Nominal SOC at delivery	27 % ²
Nominal Charge/Discharge Rate	0.5 P / 0.5 P
Round Trip Efficiency	≥ 94 %

¹ 0.5 P / 0.5 P

² 25 °C +/- 2 °C
(73.4 °F ... 80.6 °F)

³ ambient temperature

MECHANICAL

Dimensions (L x W x H)	6,058 x 2,438 x 2,896 mm (238.5 x 96.0 x 114.0 in)
Maximum Weight	40,000 kg (88184.9 lbs)
Protection Level	IP 55

TEMPERATURE RANGE

Operating	-30 °C ... 55 °C ³ (-22 °F ... 131 °F)
Storing (recommended)	-20 °C ... 35 °C ³ (-4 °F ... 95 °F)

PRODUCT CERTIFICATIONS

Certificates and Reports	IEC 62619, IEC 62477, IEC 63056, IEC 61000, UL 1973, UL 9540A, NFPA 855
Safe Transportation	UN 38.3

ENVIRONMENTAL

Compliance	RoHS, REACH, Cobalt free
Battery Regulation (EU)	2023/1542

COMPANY CERTIFICATIONS

ISO 9001, ISO 14001,
ISO 45001, SA 8000

HiTHIUM Energy Storage Technology USA Inc.

Address: 4046 Clipper Ct, Fremont, CA 94538, United States
Email: hithium@hithium.com

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone,
Xiamen, Fujian, China | Email: hithium@hithium.com



LinkedIn



Website