

# ESS Container

## 4,180 MWh

Liquid-cooled energy storage system



**Liquid-cooled energy storage system based on HiTHIUM prismatic LFP ESS Cells 314 Ah with very high cyclic lifetime.**

Improved safety characteristics and specially optimised for the highest requirements on safety, reliability and performance. Suitable e.g. for industrial, utility, and grid serving applications.

- Product certification and compliance: IEC 62619, IEC 62477, IEC 63056, IEC 61000, UL 1973, UL 9540A, NFPA 855, UN 38.3
- Company certifications: ISO 9001, ISO 14001, ISO 45001
- Environmental Compliance: RoHS, REACH, Cobalt free
- Flexible solution: String or central PCS compliance.

**High safety**

- High thermal stability thanks to liquid cooling
- Multi-stage, active fire protection system, compliance to NFPA 855
- Use of highly safe prismatic HiTHIUM LFP cells
- Dedicated cell monitoring and protection system

**Low LCOS (Levelised Cost of Storage)**

- Excellent thermal management improves energy throughput by ensuring optimal operating temperature
- Highly integrated: including thermal management system, fire protection system, BMS, etc.
- Supports back to back and side by side installations

# ESS Container

## 4,180 MWh

Liquid-cooled energy storage system based on prismatic LFP cells with very high cyclic lifetime



### GENERAL

Configuration	5*2P416S
Cooling Method	Liquid Cooling
BMS Communication	CAN, RS485, Ethernet
Gravimetric ED	≥ 119 Wh/kg
Volumetric ED	≥ 97 Wh/L
Application Altitude	≤ 4.000 m

### ELECTRICAL

Nominal Voltage	1.331,2 V
Operating Voltage	1.040 V ... 1.500 V
Nominal Energy	4.180 kWh <sup>1,2</sup>
Nominal SOC at Delivery	27 % <sup>2</sup>
Nominal Charge/Discharge Rate	0,5 P / 0,5 P
Round Trip Efficiency	≥ 94 % <sup>1,2</sup>

<sup>1</sup> 0,5 P / 0,5 P

<sup>2</sup> 25 °C +/- 2 °C

<sup>3</sup> ambient temperature

### MECHANICAL

Dimensions (L x W x H)	6.058 x 2.438 x 2.896 mm
Maximum Weight	35.000 kg
Protection Level	IP 55

### TEMPERATURE RANGE

Operating	-30 °C ... 55 °C <sup>3</sup>
Storing (Recommended)	-20 °C ... 35 °C <sup>3</sup>

### PRODUCT CERTIFICATIONS AND COMPLIANCE

Certificates, Report and Compliance	IEC 62619, IEC 62477, IEC 63056, IEC 61000, UL 1973, UL 9540A, NFPA 855
Safe Transportation	UN 38.3

### ENVIRONMENTAL

Compliance	RoHS, REACH, Cobalt free
Battery Regulation (EU)	2023/1542

### COMPANY CERTIFICATIONS

ISO 9001, ISO 14001, ISO 45001, SA 8000

**HiTHIUM Energy Storage Technology Deutschland GmbH**  
 Website: <https://hithium.com> | Email: [Contact@hithium.de](mailto:Contact@hithium.de)  
 Address: Landsberger Str. 155, 80687 Munich, Germany

**Xiamen HiTHIUM Energy Storage Technology Co., Ltd.**  
 Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone, Xiamen, Fujian, China | Email: [hithium@hithium.com](mailto:hithium@hithium.com)



LinkedIn



Website