

## ESS Cell 314 Ah

# Prismatic LFP cell optimised for use in stationary ESS



## Prismatic LFP cell with very high cyclic lifetime and improved safety characteristics.

Specially optimised for use in stationary battery storage systems with the highest requirements on safety, reliability and performance. Suitable e.g. for industrial, utility, and grid serving applications.

- Product certifications:IEC 62619, UL 9540A, UL 1973, GB/T 36276, UN 38.3
- Company certifications: ISO 9001, ISO 14001, ISO 45001, SA 8000
- Environmental Compliance: RoHS, REACH, Regulation (EU) 2023/1542, Cobalt free

#### **High safety**

- HiTHIUM-developed prismatic LFP cell with high thermal stability.
- No fire or explosion during nail penetration and crush tests
- Ultra wide operating temperature range

#### **Low LCOS (Levelised Cost of Storage)**

■ Very high cyclic lifetime ≥ 13.000 cycles, thanks to advanced material and process technologies

#### Flexible and versatile use

### ESS Cell 314 Ah

Prismatic LFP cell optimised for use in stationary ESS



GENERAL	
Nominal Capacity	314 Ah <sup>1, 2</sup>
Nominal Energy	1.004,8 Wh <sup>1, 2</sup>
Cell Chemistry	LiFePO <sub>4</sub> (LFP)
Nominal Cycles	≥ 13.000 <sup>1,2,3</sup>
Gravimetric ED	≥ 173,2 Wh/kg
Volumetric ED	≥ 382,6 Wh/L
Cell Model	LFP71173207/314Ah

ELECTRICAL		
Nominal Voltage	3,2 V <sup>1,2</sup>	
Operating Voltage	T > 0°C 2,50 3,65 V	
	T ≤ 0 °C 2,00 3,65 V	
AC Resistance (1 kHz)	0,20 mΩ +/- 0,05 <sup>4</sup>	
Max. Self-discharge Rate	3 %/month <sup>2,4</sup>	
Nominal Continuous Charge Rate	0,5 P	
Nominal Continuous Discharge Rate	0,5 P	

1	0,5	P	10,	5	Р
---	-----	---	-----	---	---

<sup>&</sup>lt;sup>2</sup> 25 °C +/- 2,0

MECHANICAL	
Dimensions (L x W x H)	174,70 x 71,70 x 207,11 mm
Туре	Prismatic
Weight	5,60 kg +/- 0,2
Volume	2,59 L

TEMPERATURE RANGE	
Charging	0°C 60°C
Discharging	-30°C 60°C
Storing (Recommended)	-20°C 35°C

PRODUCT CERTIFICATIONS		
Safety Certificates	IEC 62619, UL 9540A, UL 1973 GB/T 36276	
Safe Transportation	UN 38.3	

ENVIRONMENTAL	
Compliance	RoHS, REACH, Cobalt free
Battery Regulation (EU)	2023/1542

COMPANY CERTIFICATIONS		
ISO 9001, ISO 14 ISO 45001, SA 80		

HiTHIUM Energy Storage Technology Deutschland GmbH

Website: https://hithium.com | Email: Contact@hithium.de Address: Landsberger Str. 155, 80687 Munich, Germany

Xiamen HiTHIUM Energy Storage Technology Co., Ltd.

Address: HiTHIUM Industrial Park, Tongxiang High Tech Zone, Xiamen, Fujian, China | Email: hithium@hithium.com





<sup>&</sup>lt;sup>3</sup> 65% SOH

<sup>&</sup>lt;sup>4</sup> 27% SOC